

CIRP ANNALS 2012 Manufacturing Technology

- Annals of the International Academy for Production Engineering
- Annales du Collège International pour la Recherche en Productique
- Berichte der Internationale Akademie für Produktionstechnik

Volume 61/1 • 2012



62nd General Assembly of CIRP 62^{ème} Assemblée Générale du CIRP 62. Mitgliederversammlung des CIRP

Hong Kong, P.R. China - August 19-25, 2012

2012



ELSEVIER

Amsterdam • Boston • London • New York • Oxford Paris • Philadelphia • San Diego • St. Louis Published by Elsevier Ltd. at:

The Boulevard, Langford Lane, Kidlington, Oxford, OX5 1GB, UK

Copyright © 2012, CIRP. Published by Elsevier Ltd. All rights reserved.

This journal and the individual contributions contained in it are protected under copyright by Elsevier Ltd., and the following terms and conditions apply to their use:

Photocopying

Single photocopies of single articles may be made for personal use as allowed by national copyright laws. Permission of the Publisher and payment of a fee is required for all other photocopying, including multiple or systematic copying, copying for advertising or promotional purposes, resale, and all forms of document delivery. Special rates are available for educational institutions that wish to make photocopies for non-profit educational classroom use.

Permissions may be sought directly from Elsevier's Rights Department in Oxford, UK: phone: (+44) 1865 843830, fax: (+44) 1865 853333, e-mail: permissions@elsevier.com. Requests may also be completed on-line via the Elsevier homepage (http://www.elsevier.com/locate/permissions).

In the USA, users may clear permissions and make payments through the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, USA; phone: (+1) (978) 7508400, fax: (+1) (978) 7504744, and in the UK through the Copyright Licensing Agency Rapid Clearance Service (CLARCS), 90 Tottenham Court Road, London W1P 0LP, UK; phone: (+44) 20 7631 5555; fax: (+44) 20 7631 5500. Other countries may have a local reprographic rights agency for payments.

Derivative Works

Subscribers may reproduce tables of contents or prepare lists of articles including abstracts for internal circulation within their institutions. Permission of the Publisher is required for resale or distribution outside the institution.

Permission of the Publisher is required for all other derivative works, including compilations and translations (please consult www.elsevier.com/permissions).

Electronic Storage or Usage

Permission of the Publisher is required to store or use electronically any material contained in this journal, including any article or part of an article (please consult www.elsevier.com/permissions).

Except as outlined above, no part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of the Publisher.

Notice

No responsibility is assumed by the Publisher for any injury and/or damage to persons or property as a matter of products liability, negligence or otherwise, or from any use or operation of any methods, products, instructions or ideas contained in the material herein. Because of rapid advances in the medical sciences, in particular, independent verification of diagnoses and drug dosages should be made.

Although all advertising material is expected to conform to ethical (medical) standards, inclusion in this publication does not constitute a guarantee or endorsement of the quality or value of such product or of the claims made of it by its manufacturer.

British Library Cataloguing in Publication Data

A catalogue record for this journal is available from the British Library

Library of Congress Cataloguing-in-Publication Data

A catalogue record for this journal is available from the Library of Congress

For information on all related publications visit the Elsevier website www.elsevier.com

Printed by Polestar Wheatons Ltd, Exeter, UK

ISSN: 0007-8506

ISSN: 1660-2773 (CIRP Annals' CD-Rom inside back cover)

Table of Contents

(2) Associate Member

(3) Corporate Member / Submitted by a Fellow

(1) Fellow

Authors:

A11 - Development of an energy consump-Session on Life Cycle Engineering tion monitoring procedure for machine tools and Assembly (A) A12 - Contribution to the environmental A1 - Production of large-area lithium-ion performance of the dry-vibratory drilling technology cells - Preconditioning, cell stacking and quality assurance J. Kurfer, M. Westermeier, C. Tammer, G. Reinhart (1) A13 - A value based evaluation method for Product/Service System using design A2 - Process development for the assembly information of microsystems with hot melt adhesives T. Sakao, M. Lindahl / J.G. Persson (1)...... 51 A. Raatz, S. Rathmann, J. Hesselbach (2) A14 - Impact of green machining strategies A3 - Force generation during friction stir on achieved surface quality welding of AA2024-T3 M. Helu, B. Behmann, H. Meier, D. Dornfeld (1), D. Trimble, J. Monaghan, G.E. O'Donnell / G. Lanza (2), V. Schulze...... 55 J. Jedrzejewski (1)..... A15 - Eco-efficiency of manufacturing A4 - The influence of spot weld position processes: A grinding case variation on geometrical quality W. Li, M. Winter, S. Kara (1), C. Herrmann 59 R. Söderberg (2), K. Wärmefjord, L. Lindkvist, A16 - Critical comparison of methods to R. Berlin...... 13 determine the energy input for discrete A5 - Determination of extended availability manufacturing processes and productivity for assembly systems J.R. Duflou (2), K. Kellens, Renaldi, Y. Guo, using existing data base W. Dewulf...... 63 A17 - Quantifying the water inventory of A6 - Reconfiguration management of machining processes remanufactured products for responding F. Zhao, J. Ogaldez, J.W. Sutherland (1) 67 to varied user needs T. Sakai, S. Takata (1) 21 Session on Cutting (C) A7 - Investigation of a multiple trigger active disassembly element H.-C. Zhang (1), J. Carrell, S. Wang, D. Tate, C1 - A new 3D multiphase FE model for micro cutting ferritic-pearlitic carbon A8 - Hollow structure snap-fit design embedded with shape memory polymer M. Abouridouane, F. Klocke (1), sheet D. Lung, O. Adams 71 H. Li, K. Jin, B. He, Y. Chen / R. Teti (1) 31 C2 - Acoustic emission for controlling drill A9 - A novel separation process for position in fiber-reinforced plastic and recycling of post-consumer products metal stacks R. Wertheim (1), U. Ben-Hanan, S. Ihlenfeldt, A. Stoll, F. Treppe, M. Wabner 75 A10 - A three dimensional system approach for environmentally sustainable C3 - Ultra-precision cryogenic machining manufacturing of viscoelastic polymers Y. Kakinuma, S. Kidani, T. Aoyama (1) 79

| C4 - Manufacture and application of ultra- | Session on Design (Dn) |
|--|---|
| small micro end mills J.C. Aurich (1), I.G. Reichenbach, G.M. Schüler 83 | |
| C5 - Heat partitioning in dry milling of steel | Dn1 - Abductive reasoning for design synthesis |
| J. Sölter, M. Gulpak / T.H.C. Childs (1) 87 | S.CY. Lu (1), A. Liu |
| C6 - Delamination reduction in drilling com- | Dn2 - Semantic-based taxonomy for immer- |
| posite materials by active backup force C.C. Tsao, H. Hocheng (2), Y.C. Chen | sive product design using VR techniques S. Makris, L. Rentzos, G. Pintzos, D. Mavrikios, G. Chryssolouris (1) |
| C7 - Cutting characteristics of PVD-coated tools deposited by Unbalanced Magnetron | |
| Sputtering method | Dn3 - Improving design for recycling – Application to composites |
| A. Hosokawa, K. Shimamura, T. Ueda (1) 95 | N. Perry, A. Bernard (1), F. Laroche, S. Pompidou 151 |
| C8 - Surface integrity analysis of machined | Dn4 - Designs that surpass imagination are |
| Inconel 718 over multiple length scales R. M'Saoubi (2), T. Larsson, J. Outeiro (2), | born from discomfort outside the knowl- |
| Y. Guo, S. Suslov, C. Saldana, S. Chandrasekar 99 | edge domain M. Nakao (2), S. Nakagawa, K. lino 155 |
| C9 - The effects of cryogenic cooling on surface integrity in hard machining: A | Dn5 - An integrated computational support |
| comparison with dry machining | for design of system architecture and service |
| D. Umbrello, F. Micari (1), I.S. Jawahir (1) 103 | H. Komoto, N. Mishima, T. Tomiyama (1) 159 |
| C10 - An energy based analysis of broach- ing operation: Cutting forces and resultant | Dn6 - Integration of manufacturing-induced |
| surface integrity | properties in product design P. Groche (1), W. Schmitt, A. Bohn, S. Gramlich, |
| H.A. Kishawy (2), A. Hosseini, B. Moetakef-Imani, V.P. Astakhov 107 | S. Ulbrich, U. Günther |
| C11 - Deep hole drilling using tools with | Dn7 - A dynamic feature information model |
| small diameters—Process analysis and | for integrated manufacturing planning and optimization |
| process design A. Zabel, M. Heilmann / H.J.J. Kals (1) 111 | Y. Li, X. Liu, J.X. Gao, P.G. Maropoulos (1) 167 |
| C12 - Coated tools' wear description in | Dn8 - Encourage non-designer's design: Continuous value creation in manufactur- |
| down and up milling based on the cutting edge entry impact duration | ing products and services |
| KD. Bouzakis (1), S. Makrimallakis, G. Katirtzoglou, | T. Hara, T. Arai (1) 171 |
| E. Bouzakis, G. Skordaris, G. Maliaris, S. Gerardis115 | Dn9 - LC-CAD: A CAD system for life cycle |
| C13 - Study of optimal cutting condition for | design |
| energy efficiency improvement in ball end | Y. Umeda (2), S. Fukushige, E. Kunii, Y. Matsuyama175 |
| milling with tool-workpiece inclination Y. Oda, M. Mori (1), K. Ogawa, S. Nishida, | 1. Watsayama |
| M. Fujishima (3), T. Kawamura 119 | Dn10 - Methods and tools that support a |
| C14 - Characterization and optimization | fast and efficient design-to-order process for parameterized product families |
| of orbital drilling of woven carbon fiber | P. Schönsleben (2) 179 |
| reinforced epoxy laminates A. Sadek, M. Meshreki, M.H. Attia (1) | |
| | Session on Electro-Physical & |
| C15 - Modeling of 3D temperature fields for oblique machining | <u>Chemical Processes (E)</u> |
| I. Lazoglu (2), C. Islam | |
| C16 - Crystallographic effect on subsurface | E1 - Electrical discharge dressing and its influence on metal bonded diamond wheels |
| damage formation in silicon microcutting | E. Weingärtner, R. Roth, F. Kuster (3), |
| J. Yan, T. Asami, H. Harada, T. Kuriyagawa / S. Shimada (1)131 | M. Boccadoro (3), F. Fiebelkorn / G. Levy (1) 183 |
| C17 - Cutting characteristics of biological | E2 - Comparison of energy and removal |
| soft tissues | efficiencies between micro and macro EDM M. Zahiruddin, M. Kunieda (1) |
| Z. Hu, B. Zhang (1), W. Sun | IVI. Zariiruddiri, IVI. Italiidda (1) |
| C18 - Five-axis milling tool path generation | E3 - Enhanced surface integrity and dimen- |
| with dynamic step-over calculation based on integrated material removal simulation | sional accuracy by simultaneous micro-ED/ EC milling |
| B. Lauwers (1), D. Plakhotnik | M.D. Nguyen, M. Rahman (1), Y.S. Wong 191 |

| E4 - Enhancement of mass transport in micro wire electrochemical machining | F5 - Sheet forming process of carbon fiber reinforced plastics for lightweight parts |
|--|--|
| YB. Zeng, Q. Yu, SH. Wang, D. Zhu (1) 195 | J. Yanagimoto (2), K. Ikeuchi |
| E5 - Machining of turbulated cooling | F6 - Accumulative-DSIF strategy for |
| channel holes in turbine blades | enhancing process capabilities in |
| J. Pattavanitch, S. Hinduja (1) 199 | incremental forming R. Malhotra, J. Cao (2), M. Beltran, D. Xu, |
| E6 - On the relationship between the dynamics of the power density and | J. Magargee, V. Kiridena, Z.C. Xia |
| workpiece surface texture in pulsed laser | F7 - Punching of small hole of die- |
| ablation | quenched steel sheets using local |
| M.C. Kong, C.B. Miron, D.A. Axinte (2), | resistance heating |
| S. Davies, J. Kell | Ki. Mori (1), T. Maeno, Y. Maruo |
| E7 - Process investigations of optical trap | F8 - Failure prediction for nonlinear strain |
| assisted direct-write microsphere near-field | paths in sheet metal forming |
| nanostructuring KH. Leitz, U. Quentin, I. Alexeev, M. Schmidt (3) / | W. Volk, H. Hoffmann (2), J. Suh, J. Kim 259 |
| L. Li (1) | F9 - Orbital forming of tailored blanks from |
| E9 Density improvement of alumina | sheet metal M. Morklein (2) B. Blottke, S. Onel |
| E8 - Density improvement of alumina parts produced through selective laser | M. Merklein (2), R. Plettke, S. Opel |
| sintering of alumina-polyamide composite | F10 - Finite element analysis of the ring |
| powder J. Deckers, JP. Kruth (1), K. Shahzad, | rolling process with integrated closed-loop control |
| J. Vleugels | V. Jenkouk, G. Hirt (2), M. Franzke, T. Zhang 267 |
| E9 - Laser patterning of thin film sensors | F11 - Analysis of fluid lubrication mecha- |
| on 3-D surfaces | nisms in metal forming at mesoscopic scale |
| L. Overmeyer, J.F. Duesing, O. Suttmann, U. Stute / H.K. Toenshoff (1) | L. Dubar, C. Hubert, P. Christiansen, N. Bay (1), |
| U. State / H.N. Toensholl (1) | A. Dubois |
| E10 - Submicrometer thickness layer | F12 - Cold joining of rotor shaft with flange |
| fabrication for layer-by-layer microstereo- lithography using evanescent light | by using plastic deformation K. Kitamura, K. Hirota, Y. Ukai, K. Matsunaga, |
| S. Takahashi (2), Y. Kajihara, K. Takamasu 219 | K. Osakada (1) |
| E11 - Freeze-form extrusion fabrication of | |
| functionally graded materials | 0 |
| M.C. Leu (1), B.K. Deuser, L. Tang, R.G. Landers, G.E. Hilmas, J.L. Watts | Session on Abrasive Process (G) |
| G.L. Hillias, J.L. Walls | |
| E12 - Prediction of tool wear in micro USM | G1 - Dressing and truing of hybrid bonded |
| Z. Yu (2), C. Ma, C. An, J. Li, D. Guo 227 | CBN grinding tools using a short-pulsed |
| | fibre laser |
| 0 | C. Walter, M. Rabiey, M. Warhanek, N. Jochum, K. Wegener (3) / R. Züst (1) |
| Session on Forming (F) | |
| | G2 - Precision grinding of structured ceramic molds by diamond wheel trued |
| F1 - On the die design in AA6082 porthole | with alloy metal |
| extrusion | H. Suzuki (2), M. Okada, Y. Yamagata, S. Morita, |
| F. Gagliardi, G. Ambrogio, L. Filice (2) 231 | T. Higuchi |
| F2 - Multi billet extrusion technology for | G3 - Development of fixed-abrasive tool |
| manufacturing bi-layered components L. Madej (2), H. Paul, L. Trebacz, W. Wajda, | with spiral groove for decreasing the loading K. Tsuchiya, Y. Kamimura, Y. Tani, S. Lee / |
| M. Pietrzyk (1) | T. Matsuo (1) |
| | The state of the s |
| F3 - High quality extrudates from aluminum chips by new billet compaction and defor- | G4 - Continuous generating grinding— Tooth root machining and use of CBN-tools |
| mation routes | J. Köhler, A. Schindler, S. Woiwode / A. Ber (1) 291 |
| W.Z. Misiolek, M. Haase, N. Ben Khalifa, | |
| A.E. Tekkaya (1), M. Kleiner (1) 239 | G5 - Grinding performance and workpiece |
| F4 - On the gas pressure forming of | integrity when superabrasive edge rout- ing carbon fibre reinforced plastic (CFRP) |
| aluminium foam sandwich panels: | composites |
| Experiments and numerical simulations | S.L. Soo (2), I.S. Shyha, T. Barnett, |
| H. Nassar, M. Albakri, H. Pan, M. Khraisheh (2) 243 | D.K. Aspinwall (1), WM. Sim |

| G6 - Abrasive points for drill grinding of | M7 - Integrated autonomous monitoring of |
|---|--|
| D. Biermann (2), M. Feldhoff | ball screw drives HC. Möhring, O. Bertram / B. Denkena (1) 355 |
| D. Biermann (2), ivi. Feidhon | 11C. Monning, C. Dertram / B. Denkena (1) 333 |
| G7 - Dual mode control of the rotational | M8 - 6D direct-drive technology for planar |
| grinding process | motion stages |
| E. Ahearne (2), D. Logan, G. Byrne (1) 303 | X. Lu, Iur. Usman / W. Tyler Estler (1) 359 |
| G8 - Prediction of bone grinding tempera- | M9 - A newly developed ripple-free |
| ture in skull base neurosurgery | precision toroidal type motor |
| A.J. Shih, B.L. Tai, L. Zhang, S. Sullivan, | H. Yoshioka, Y. Kurisaki, H. Sawano, |
| S. Malkin | H. Shinno (1) |
| G9 - Magnetic abrasive finishing of cutting | M10 - Real-time monitoring of pressure |
| tools for machining of titanium alloys | distribution in microrolling through |
| H. Yamaguchi, A.K. Srivastava (3), M.A. Tan, | embedded capacitive sensing |
| R.E. Riveros, F. Hashimoto (1) 311 | Z. Fan, MK. Ng, R.X. Gao (2), J. Cao (2), |
| G10 - Dynamic multiphase modeling and | E.F. Smith III |
| optimization of fluid jet polishing process | M11 - Ultra-precision finishing of micro- |
| A. Beaucamp, Y. Namba, R. Freeman / | aspheric mold using a magnetostrictive |
| J. Bryan (1) | vibrating polisher |
| , | J. Guo, Sy. Morita, M. Hara, Y. Yamagata, |
| G11 - Macroscopic simulation of the liner | T. Higuchi / T. Hoshi (1) |
| honing process | |
| B. Goeldel, M. El Mansori, D. Dumur (1) 319 | M12 - Mechanism of surface modification using machine hammer peening technology |
| G12 - Prevention of wheel clogging in | F. Bleicher, C. Lechner, C. Habersohn, |
| creep feed grinding by efficient tool cleaning | E. Kozeschnik, B. Adjassoho, H. Kaminski / |
| C. Heinzel (2), G. Antsupov | G. Pritschow (1) |
| | |
| G13 - Study of tribo-chemical lubricant | M13 - Sacrificial structure preforms for thin |
| film formation during application of nano- | part machining |
| lubricants in minimum quantity lubrication | S. Smith (1), R. Wilhelm (2), B. Dutterer, |
| (MQL) grinding P. Kalita, A.P. Malshe (2), K.P. Rajurkar (1) 327 | H. Cherukuri, G. Goel |
| F. Kalita, A.F. Maistie (2), K.F. Kajurkai (1) 321 | M14 - Raw part characterisation and |
| | automated alignment by means of a |
| 0 ' 11 (11) | photogrammetric approach |
| Session on <u>Machines (M)</u> | M. Zatarain (1), A. Mendikute, I. Inziarte 383 |
| | |
| M1 - A novel tool path/posture optimiza- | Session on Production Systems |
| tion concept to avoid chatter vibration in | |
| machining – Proposed concept and its | and Organizations (O) |
| verification in turning | |
| E. Shamoto (2), S. Fujimaki, B. Sencer, N. Suzuki, | |
| T. Kato, R. Hino | O1 - A risk management-based approach |
| M2 - Contour error control of CNC machine | for inventory planning of engineering-to- |
| tools with vibration avoidance | order production |
| Y. Altintas (1), M.R. Khoshdarregi | A.M. Radke, M.M. Tseng (1) |
| an annual reactions and A fortunation of the annual reaction of the | O2 - Categorization and mechanism of |
| M3 - Prediction of workpiece dynamics and | platform-type product-service systems in |
| its effects on chatter stability in milling | manufacturing |
| E. Budak (1), L.T. Tunç, S. Alan, H.N. Özgüven 339 | N. Nishino, S. Wang, N. Tsuji, K. Kageyama, |
| M4 - Investigation of spindle bearing | K. Ueda (1) |
| preload on dynamics and stability limit in | O2 Internated severity alonging |
| milling | O3 - Integrated capacity planning over highly volatile horizons |
| E. Ozturk, U. Kumar, S. Turner, T. Schmitz / | G. Lanza (2), S. Peters |
| M.A. Davies (1) | J. Lanza (2), J. 1 Gloid |
| 79° | O4 - Method for energy and resource bal- |
| M5 - Design- and control-concept for com- | ancing demonstrated as an example of the |
| pliant machine tools based on controller | hot sheet metal production process |
| integrated models | A. Göschel (3), F. Schieck, J. Schönherr / |
| E. Uhlmann (1), J. Eßmann, JH. Wintering 347 | R. Neugebauer (1) |
| M6 - Improvement of feed drive dynamics | O5 - Simulation based comparison of |
| by means of semi-active damping | safety-stock calculation methods |
| A. Verl (2), S. Frey 351 | |

| O6 - Versatile autonomous transportation vehicle for highly flexible use in industrial applications J. Franke, F. Lütteke / K. Feldmann (1) | O20 - A proposal on optimized scheduling methodology and its application to an actual-scale semiconductor manufacturing problem T. Kaihara (2), S. Kurose, N. Fujii |
|---|---|
| O7 - Decision support systems for effective maintenance operations J. Ni, X. Jin / Y. Koren (1) | Session on Precision Engineering and Metrology (P) |
| O8 - A method for determining a functional unit to measure environmental performance in manufacturing systems J. Plehn, R. Züst (1), F. Kimura (1), A. Sproedt, P. Schönsleben (2) | P1 - A noncontact scanning electrostatic force microscope for surface profile measurement W. Gao (2), S. Goto, K. Hosobuchi, S. Ito, |
| O9 - Using probabilistic relational models for knowledge representation of production systems: A new approach to assessing maintenance strategies B. lung (2), G. Medina-Oliva, P. Weber, E. Levrat 419 | Y. Shimizu |
| O10 - Discovering autonomous structures within complex networks of work systems R. Vrabič, D. Husejnagić, P. Butala (2) | P3 - Dimensional measurement of micro- form with high aspect ratio using an optically controlled particle with standing wave scale sensing |
| O11 - A multi-criteria evaluation of central- ized and decentralized production networks in a highly customer-driven environment | Y. Takaya (2), M. Michihata, T. Hayashi, T. Washitani |
| D. Mourtzis (2), M. Doukas, F. Psarommatis 427 O12 - Cost innovations by integrative product and production development | tion of contact pressure and stress J. Solle, JM. Linares (2), JM. Sprauel, E. Mermoz (3) |
| A. Kampker, G. Schuh (1), P. Burggräf, C. Nowacki, M. Swist | P5 - Universal high precision reference spheres for multisensor coordinate measuring machines C.P. Keferstein (3), M. Marxer, R. Götti, R. |
| smart interlocking software blocks A. Nassehi, S.T. Newman (2) | Thalmann, T. Jordi, M. Andräs, J. Becker / L. de Chiffre (1) |
| O14 - Design and assessment of quality control loops for stable business processes R. Schmitt (2), L. Monostori (1), H. Glöckner, Z.J. Viharos | P6 - Accuracy of industrial computed tomography measurements: Experimental results from an international comparison S. Carmignato / L. De Chiffre (1) |
| O15 - Combination of planning methods in a comprehensive production planning approach for sequenced production lines K. Matyas, S. Auer / HJ. Warnecke (1) | P7 - Sense and non-sense of beam hardening correction in CT metrology W. Dewulf, Y. Tan, K. Kiekens / P. Vanherck (1) 495 |
| O16 - Scheduling with alternative routings in CNC workshops Y. Nonaka (3), G. Erdős, T. Kis, T. Nakano (3), | P8 - Three-dimensional holistic approximation of measured points combined with an automatic separation algorithm K. Lübke, Z. Sun, G. Goch (1) |
| J. Váncza (1) | P9 - A methodology for the quantification of value-adding by manufacturing metrology E. Savio (2) |
| asynchronous manufacturing systems with degrading machines M. Colledani, T. Tolio (1) | P10 - Integrating the continuous improve- ment of measurement systems into the |
| O18 - Energy-aware scheduling for improving manufacturing process sustainability: A mathematical model for flexible flow shops A.A.G. Bruzzone (1), D. Anghinolfi, M. Paolucci, | statistical quality control of manufacturing processes: A novel link M. Villeta, E.M. Rubio (3), J.L. Valencia, M.Á. Sebastián (3) / R. Bueno (1) |
| F. Tonelli | P11 - Nano fabrication of star structure for precision metrology developed by focused ion beam direct writing |
| factory planning process D. Chen, S. Heyer, G. Seliger (1), T. Kjellberg (1) 463 | Z. Xu, F. Fang (1), H. Gao, Y. Zhu, W. Wu, A. Weckenmann (1)511 |

| P12 - Five-axis machine tool calibration by probing a scale enriched reconfigurable uncalibrated master balls artefact J.R.R. Mayer / M. Balazinski (1) | S7 - Evaluation of process causes and influences of residual stress on gear distortion R. Husson, JY. Dantan (2), C. Baudouin, S. Silvani (3), T. Scheer, R. Bigot |
|---|---|
| P13 - Machining of optical freeform prisms by rotating tools turning X. Zhang, H. Gao, Y. Guo, G.X. Zhang (1) 519 | S8 - The influence of process vibrations on precision polishing metrics B. Mullany (3), M. Mainuddin / C. Evans (1) 555 |
| P14 - Multivariate sensing and wireless data communication for process monitoring in RF-shielded environment R.X. Gao (2), D.O. Kazmer | S9 - Alternative strategies in finishing cylinder running surfaces B. Karpuschewski (1), HJ. Pieper, F. Welzel, K. Risse |
| Session on Surfaces (S) | S10 - Manufacture of functional surfaces through combined application of tool man- ufacturing processes and Robot Assisted Polishing R.S. Eriksen, M. Arentoft (2), J. Grønbæk, |
| S1 - Generalized form characterization of ultra-precision freeform surfaces | N. Bay (1) |
| C.F. Cheung, L. Kong, M. Ren, D. Whitehouse (1), S. To | S11 - A study on the quality of micro- machined surfaces on tungsten carbide generated by PCD micro end-milling |
| S2 - Automated surface inspection of cold-formed micro-parts B. Scholz-Reiter (1), D. Weimer, H. Thamer 531 | K. Nakamoto, K. Katahira, H. Ohmori (2), K. Yamazaki (1), T. Aoyama (1) 567 |
| S3 - Surface wear of TiN coated nickel tool during the injection moulding of polymer micro Fresnel lenses G. Tosello (2), H.N. Hansen (1), S. Gasparin, | S12 - Highly wear-resistant cutting tools with textured surfaces in steel cutting T. Enomoto (2), T. Sugihara, S. Yukinaga, K. Hirose, U. Satake |
| J.A. Albajez, J.I. Esmoris | S13 - Laser-assisted nano particle deposition system and its application |
| S4 - Influence of rapid mold temperature variation on surface topography replication and appearance of injection-molded parts G. Lucchetta, M. Fiorotto, P.F. Bariani (1) 539 | for dye sensitized solar cell fabrication SH. Ahn (2), JO. Choi, CS. Kim, GY. Lee, HT. Lee, K. Cho, DM. Chun, C.S. Lee 575 |
| S5 - Cryogenic deep rolling – An energy based approach for enhanced cold surface | S14 - Influence of surface properties on bioactivity and pull-out torque in cold thread rolled Ti rod—Development of |
| hardening D. Meyer / E. Brinksmeier (1) 543 | bioactive metal-forming technology Y. Yoshida, K. Kuroda, R. Ichino, N. Hayashi, N. Ogihara, Y. Nonaka / Y. Tozawa (1) 579 |
| S6 - Prediction of machining induced | |
| residual stresses in turning of titanium and nickel based alloys with experiments and finite element simulations | S15 - Significant improvement of corro- sion resistance of biodegradable metallic implants processed by laser shock peening |
| T. Özel (2), D. Ulutan 547 | Y. Guo, M.P. Sealy, C. Guo (2) 583 |
| | |

FISEVIER

Contents lists available at SciVerse ScienceDirect

CIRP Annals - Manufacturing Technology

journal homepage: http://ees.elsevier.com/cirp/default.asp



Combination of planning methods in a comprehensive production planning approach for sequenced production lines

Kurt Matyas a,*, Stefan Auer b

Submitted by: Hans-Juergen Warnecke (1) Stuttgart, Germany.

ARTICLE INFO

Keywords: Production planning Sequencing Program planning

ABSTRACT

Medium-term sales and operations as well as medium to short-term production planning in customer order driven production processes are performed using a cascading planning process. A lack of coordination and feedback between different planning phases causes problems with a negative effect on costs in production that originate from unfeasible production programs. Based on a system for the classification of planning restrictions the planning process will be controlled utilizing a newly developed combination of the methods of Linear Programming and Constraint Programming. The result is a formal logic to combine the different planning horizons and the two sets of planning methods.

@ 2012 CIRP.

1. Introduction

In the European automotive and mechanical engineering industry an effective management of order processing, in particular regarding data processing and information exchange will be an increasing success factor [1]. In these industrial sectors various systems for sales planning, purchasing, production and supply chain management are employed, which are often poorly synchronized or even incompatible [2].

That entails, it is common to plan the different steps in a chain sequentially while at the same time, in the whole planning process, a broad variety of types and combinations of options have to be considered. One of the planning requirements is a high accuracy concerning i.e. workstations, human resources and material. Currently planning, especially in the automotive sector, but in different industries as well, is conducted in cascades. This poses the problem of a lack of coordination and feedback between the planning steps, which may cause contradictions in the production programs. As a result, short-term troubleshooting has to take place and additional or different resources must be procured [2].

The aim of this paper is to describe a method of achieving a harmonized planning process for sequenced production lines through the combination of planning methods and the timely consideration of constraints of a cascadic planning. The solution presented herein represents a tool with which different domains communicate with each other. The tracking of bottlenecks and timely detection of problems will be ensured, enabling a proper reaction.

Therefore Section 2 summarizes the relevant planning processes for order driven production in sequenced production lines. The gap of existing solutions and the reason for the development of the method are depicted. In Section 3 the principles of existing solving algorithms are described and possibilities of an integration of sequencing rules in program planning are shown. Section 4

describes how the planning processes and the combination of program planning and sequencing steps will be executed. Section 5 summarizes the results and gives an outlook to further activities.

2. Planning process for sequenced production lines

In customer order driven production processes the key target of planning is to align market requirements with available production factors. Production restrictions in long- and mid-term planning are fixed and production factors are limited according to context-related restrictions [3].

In Fig. 1, a planning cascade of a synchronized production line is described, where several production factors have to be taken into account on different levels of aggregation [4]. Depending on the planning horizon, the planning process starts from rough estimations and ends with the manufacturing- or the assembly process. Tasks and restrictions have to be adjusted to avoid conflicts such as bottlenecks or under-utilization of the production factors.

The planning process starts with a market analysis. After that follows an annual budget planning that results in sales forecasts, which are continuously updated. This step is succeeded by the generation of a rough production plan allocating, for example, production orders to order pools. Finally in the short term planning horizon a detailed order sequence has to be defined.

The planning gradually gets more detailed with each step. For example, in the very beginning (program planning) dummy orders are assumed, based on various sales prognoses etc. gradually being replaced by real orders, the further the planning proceeds [5]. Simultaneously, the constraints for the planning process become tighter with the production date approaching.

The development of an integrated planning approach as the basis of a software tool that harmonizes the planning tasks over the different planning horizons is subject of an ongoing research project called HarmoPlan. This paper presents the application of the new developed integrated planning approach that is based on a

a Institute of Management Science, Vienna University of Technology, Theresianumgasse 27, 1040 Vienna, Austria

^b Fraunhofer Austria Research Gmbh, Division of Production and Logistics Management, Theresianumgasse 7, 1040 Vienna, Austria

^{*} Corresponding author.




Fig. 1. Planning tasks and interrelationship with fundamental factors, product and market [4].

classification of the origins of planning constraints. The resulting software tool is to bridge the usually employed planning cascade.

This can be achieved by shifting later occurring constraints to an earlier planning stage. Therefore, the so called Constraint Manager is required. This newly developed tool combines necessary constraints in a standardized format and even enables tracing the originator of each of these constraints. The application of filters winnows irrelevant constraints, leaving the focus on the important ones. The constraint Manager even indicates the necessity for preplanning by searching for a reason as soon as a constraint is ignored or exceeded [3].

3. Solving algorithms

In the following, typical algorithms and solving solutions are presented, which are used for dealing with problems in program planning and sequencing. After that a possibility to draw restrictions from sequencing to the earlier stages of program planning is introduced. This systematic supports the basis to approach the planning problem. Subsequently, the paper focuses on the description of how the single planning tasks in the planning system have to be integrated to be used operatively. That means how the restrictions have to be defined so that they can be executed in both planning problems.

3.1. Program planning

Usually, short-, mid- and long-term production planning are being distinguished in planning. While long- and mid-term planning most notably are determined in a qualitative way, the short term planning determines the production program quantitatively (quantity per time).

In the relevant literature several approaches and algorithms for the planning tasks can be found. The following basic mixed-integer programming model for master scheduling, suggested by Boysen et al. [6] is proposed to minimize deviation costs.

The objective function (1) considers deviation costs for all orders i assigned to period t (x_{it} = 1). The variables in the equation are the number of product orders N (n = 1,...,N) (2) which have to be regarded and the planning periods T (t = 1,...,T) (3).

$$Minimize z_i = \sum_{t=1}^{N} \sum_{t=1}^{T} c_{it} x_{it}$$
(1)

$$\sum_{t=1}^{T} x_{it} = 1 \quad \forall_{i} = 1, \dots, N$$
 (2)

$$\sum_{i=1}^{N} x_{it} \le P \quad \forall_{t} = 1, \dots, T$$
 (3)

For the calculation of the deviation costs, inventorying holding costs, the date of delivery and late delivery penalty costs are being taken into account. x_{it} is the factor for the information, if an order i is allocated with a time period t. $x_{it} = 1$ if this is true and $x_{it} = 0$ if there is no allocation (5). If Eq. (2) is fulfilled, it is guaranteed, that every order is fulfilled in one certain production period, while

Eq. (3) simply states, that a limited amount of production period *P* must not be exceeded.

Further, B_{qt} from Eq. (4) deals with the availability of components. It stands for the number of available components which states a maximum. The coefficient of demand b_{iq} states, that if a certain component is a part of an order, it can either be 0 or bigger. Q stands for the sum of all relevant components of a product whilst q is one specific component [6].

$$\sum_{i=1}^{N} b_{iq} \times x_{it} \le B_{qt} \quad \forall q \in Q_i t = 1, \dots, T$$
(4)

$$x_{it} \in \{0, 1\} \quad \forall i = 1, \dots, N; t = 1, \dots, T$$
 (5)

3.2. Sequencing

For solving the sequencing problem, three different solutions are described in the literature.

Level scheduling – based on the principles of the Toyota-Production-System – is a method that aims to achieve a smooth distribution of the material demand [7]. Another sequencing method is the so called mixed-model sequencing that reduces overloads of resources in the system. Therein an exact schedule of each type and station, under consideration of the type specific work content, is calculated [8–12].

Within the research project HarmoPlan a constraint programming approach for the car sequencing problem is used. The restrictions for the car sequencing are on the one side that an order is connected to a certain type v ($v = 1, \ldots, V$) in the cycle t ($t = 1, \ldots, T$) which is expressed by x_{vt} and can take the value 0 or 1. On the other side it has to be assured, that in each cycle exactly one option is being produced. If a constraint is added, that assures, that only H_o products in a series of N_o products have the same option o, the result is a model for the sequential arrangement [13].

$$\sum_{t=t'}^{t' \to N_o - 1} \sum_{v=1}^{V} x_{v1} \times a_{vo} \le H_o \quad \forall o = 1, \dots 0; \ t' = 1, \dots, T - N_o + 1 \quad (6)$$

Here a_{vo} is the demand of option o in type v. It has to be noted, that one type can have different options (o = 1,...,0) [6].

3.3. Possibilities of an integration of sequencing rules in program planning

To integrate sequencing rules into the program planning, following condition is suggested as a basis for integrated planning [8]:

$$\sum_{i=1}^{N} d_{io} \times \chi_{it} \le \alpha \times \frac{H_o}{N_o} \times P \quad \forall_0 \in 0; t = 1, \dots, T$$
 (7)

 d_{io} = demand factor; α = scaling factor.

Eq. (7) however represents only a reasonable and not a necessary condition for a solvable sequencing problem. Nonetheless, the knowledge about the single approaches for the solution is just the first step for the development of a comprehensive production planning approach. It is essential to fill up these algorithms with suitable inputs such as defining capacity constraints as well as other planning restrictions.

4. Applicable comprehensive planning approach

This part describes how the planning processes and the combination of program planning and sequencing steps will be executed. Therefore the overall planning approach is presented. The most challenging task for the comprehensive planning approach is to make planning restrictions of one planning task available in the other planning tasks. This mapping of constraints is also described in the following part.

4.1. Planning approach

The overall goal of the research project HarmoPlan is to define and develop a planning system that supports comprehensive planning throughout the different levels. This approach has to take into account shifting responsibilities and different levels of abstraction along the planning cascade (e.g. sales is planning on the level of car volumes in order to meet market requirements, production planning is dealing with planning objects such as specific car configurations or bills of materials to optimally utilize production capacities). Due to the high complexity of the planning problem for a tool that covers all planning processes from long-, mid- to short-term planning, current systems do not integrate planning constraints throughout the whole planning cascade. Therefore the presented approach is meant to introduce a realizable solution to convert planning constraints for consideration in each planning task [4].

As every single planning step is dealing with various input data depending on the planning horizon, the planned quantities are presented as monthly, weekly and daily volumes or order pools in long- and mid-term or as order sequences in short-term planning.

In order to align the existing capacities with the customer requirements and to identify bottlenecks as early as possible, constraints of subsequent planning tasks need to be available for each planning step and in each required configuration. Therefore, the constraints caused by the earlier described originators are stored within the already developed so called constraint manager, a database that collects the constraints and stores them in a standardized format [3].

When a planning task has to be executed all relevant planning constraints can be taken into account.

Due to a higher number of constraints than in the original planning task it is possible that the planning problem is too complex and no solution fulfilling all constraints exists. Therefore the constraints have an attribute that classifies whether the constraint is "hard" or "soft". First the used planning algorithms try to find a solution considering hard and soft constraints. If no solution can be derived, the planning problem is relaxed and only hard constraints will be considered. Planning constraints of following planning steps will usually be classified as soft constraints. In order to evaluate different planning results, each constraint owns an attribute that defines a penalty in case of a violation. More important constraints have a higher penalty rate than others.

After the execution of the planning task the planner has an overview of all violations. So, if a constraint cannot be fulfilled, the planner is able to identify the reason and can set possible countermeasures to widen the bottleneck – or to solve the problem by a re-planning, considering a different constraint setting. Fig. 2 shows the concept of the planning workflow that will be covered within one planning tool.

One task of the research project was to identify, which of the constraints should be available in other planning steps. During the project it turned out that if valid order pools are passed to the next planning step, constraints do not need to be considered again. If major changes are necessary the previous planning step has to be executed again.

4.2. Creation and handling of planning constraints

The following part about the creation and handling of constraints will focus on the combination of program planning and sequencing. The topic of the research project also covers the integration of sales planning. The procedure for integrating sales planning is analog to the approach described within this paper.

The described classification of constraints in Fig. 2 gives an overview on possible restriction types. However, so far there is no categorization, on which restrictions have to be taken into account in which planning step.

Within the program planning capacity constraints are usually taken into account. On the one hand this can include capacity restrictions according to factory calendar, working hours and cycle times. On the other hand the part availability is important and also covered by capacity restrictions. In some cases also staff sizing problems can be included within the program planning algorithm [5].




Fig. 2. Planning approach.

There are also a high number of possible sequencing rules. In order to show how the conversion of constraints works, three constraint types are described in detail:

- Distance constraint: This constraint type defines a minimal or maximal distance for two vehicles with the same value (e.g. a vehicle with a sunroof cannot be followed by another vehicle with sun roof).
- Block constraint: Such constraints aim at building blocks of vehicles with special values within the sequence. This rule can be useful for planning a color sequence in the paint shop or to build blocks of vehicles where extra personnel is required on a special assembly station.
- Distance constraints for different options define the distance of two vehicles in the assembly sequence with different values (e.g. a car with a sun roof cannot be followed by a convertible car).

Other sequencing rules can aim on an even distribution of options, can limit the amount of options per day or shift, or can define a sequence position for vehicles with a special option, etc.

For the definition of rules that have to be considered in both, program planning and sequencing, a whole bunch of attributes is crucial. A list and classification of those attributes is given in the following. This classification tries to describe the different types of rules in a uniform mode, so that they can be featured in a database. As listing all attributes would exceed this paper, only the above mentioned constraints are described herein., The research project however dealt with a far broader range of restrictions.

The database is structured in common attributes, sales planning attributes, program planning attributes and attributes concerning sequencing.

If a restriction is created, is the restriction type has to be selected. With this choice, it is only necessary to enter attributes that are relevant for that certain type. Furthermore, the conversion logics are being activated and additional fields of the restriction are being complemented automatically.

- **General attributes**: These attributes are required for every constraint within the system and allow for an identification of the constraint. Typical attributes are name or constraint ID, textual description, constraint type, affected assembly plant, sales region, vehicle type, validity period and value.
- Program planning attributes: For the described capacity constraints, minimum and maximum values are required.
 Furthermore, a classification (hard or soft constraint) and a penalty for rule violation need to be defined.
- Sequencing attributes: For sequencing also minimum and maximum values, classification and penalty are necessary attributes. In order to fully specify the previously described constraints, also block length, block distance and a second value are compulsory attributes.