

Selecting efficient support methods for tunnels



Construction of a tunnel consists of many activities during the construction phase of the project, supporting is one of these activities.

Hossam TOMA¹ and Hans G. JODL²

ImmEDIATE support elements are provided to control ground movement caused by stress redistribution during tunnel drive. Certain support elements are assembled in the excavated areas of crown, side wall and additionally on the tunnel face if necessary. Typical support elements are rock bolts, reinforced sprayed concrete, girders, etc. Loose ground and weak rock within the following rounds can also be supported using methods such as pipe umbrella, forepoling, earth wedge, etc. The Selection of efficient support methods for tunnelling is very important to reduce problems during construction and maintain project cost and time within the project budget and the planned schedule. This paper introduces a model that helps decision maker in selecting tunnel support methods in the conceptual phase of the project. The model calculates efficiency percentages of support methods based on project conditions. The model provides the user with a report including support methods and their efficiency percentages ranked in descending order.

„Introduction“

Support of tunnel side walls and crown as well as tunnel face is very essential when the tunnel is constructed in weak ground. Lauffer (1958) proposed that the stand-up time for an unsupported span is related to the qua-

lity of the ground in which the span is excavated. In a tunnel, the unsupported span is defined as the span of the tunnel or the distance between the face and the nearest support, if this is greater than the tunnel span. When the excavated ground is hard rock the stand-up time can reach, in some cases, up to years. Weak ground which has a short stand-up time –might be less than 1 hour– needs to be supported immediately after excavation. There are several methods which can be used for tunnel side wall and crown support, these methods are rock bolts, dowels, steel arches, sprayed concrete, and precast concrete segments. Forpoling, pipe umbrella, doorframe slab, earth wedge, and sprayed concrete can also be used for supporting the tunnel face.

Selection of an efficient support method is a key factor for the success of the tunnel project. Efficient method is the method which satisfies efficiently the controlling factors which are technical and non-technical factors.

Almost all the empirical models that are used for determining support methods are related to the ground classification systems. Written rules for selecting ground support were first formulated in 1946 by Terzaghi. Deere et al (1970) presented ground support recommendations for tunnels excavated conventionally and by TBMs based on both of Terzaghi's classification and

¹ Assistant Professor, Department of Construction Engineering and Utilities, Faculty of Engineering, Zagazig University, Zagazig, Egypt. E-mail address: hossam.toma@gmail.com

² Professor and Head of Institute of Interdisciplinary Construction Process Management, Faculty of Civil Engineering, Vienna University of Technology, Vienna, Austria. E-mail: jodl@ibb.tuwien.ac.at



the Rock Quality Designation index (RQD). Wickham et al (1972) suggested also support methods for tunnels during construction based on the Rock Structure Rating (RSR) classification system. The above mentioned systems are not widely used now but they were the nucleus for the newer systems. The Geomechanics Classification or the Rock Mass Rating (RMR) system, which first published by Bieniawski in 1976, and its modifications in 1989 (Bieniawski (1989)) suggest guidelines for the selection of support in tunnels in rock for which the value of RMR has been determined. In 1974, Barton et al proposed a Tunnelling Quality Index (Q) for the determination of rock mass characteristics and tunnel support requirements, this system was updated by Grimstad and Barton (1993) to reflect the increasing use of steel fibre reinforced sprayed concrete in underground excavation support. The guideline for geomechanical design of cyclic tunnelling (Austrian Society for Geomechanic, 2001) considers decisive geomechanical factors. All the above mentioned systems suggest support methods based only on the ground conditions ignoring other factors that may have a significant weight in choosing the support method. The introduced model takes into consideration the most important factors that may have influence on the selection of the support methods.

„Selecting efficient support method model.“

The proposed model represents a quantitative calculational preselection of an efficient tunnel support method assisting decision makers in the conceptual phase of the project. The model

Support Methods		Side wall & Crown support					Face support					
		Rock bolts	Dowels	Steel arch	Sprayed concrete	Precast concrete segments	Forepoling	Pipe umbrella	Doorframe slab	Earth wedge	Sprayed concrete	
Factors	Ground conditions	Ground is soil										
		Rock quality (RMR values)	0 - 20									
			21 - 40									
			41 - 60									
			61 - 80									
	Over 80											
	Prevent failure	Failure due to weathering										
		Failure due to moving water										
		Failure due to corrosion of support										
		Failure due to squeezing & swelling										
Failure due to overstress												
Tunnel depth	Less than 30m											
	30 - 50m											
	50 - 100m											
	100 - 500m											
	500 - 1000m											
	Over 1000m											
Constructibility	Circular or mouth cross section											
	Oval or Horseshoe cross section											
	Other cross sections											
	Tunnel span	Less than 1.5m										
		1.5 - 4m										
4 - 6m												
6 - 10m												
Over 10m												
Tunnel excavation methods	Excavator / Front shovel / Backhoe											
	Hand excavation											
	Drill & blasting											
	Roadheader											
	Micro-tunnelling machine											
	Shield machine											
TBM (open machine)												

Table (1): Comparing between support methods based on technical factors

calculates efficiency percentages (EPs) of the support methods for controlling factors which represent project's technical and non-technical conditions. Calculation of the EP for a support method depends on two factors which are the efficiency degrees (EDs) of the method for the particular controlling factors and the importance percentages (IPs) of the controlling factors.

Controlling factors: Four technical factors are used to represent the main projects' technical conditions which control the selection of support methods, these factors are ground conditions, tunnel depth, constructibility, and tunnel excavation method (Toma, 2005). Non-technical factors are cost and time. Three matrices - tables (1), (2) and (3) - were developed to combine the controlling factors and support methods. The matrices were sent to tunnel experts working for 35 construction companies, 28 designers, and 12 clients. Tunnel experts of these organizations were asked to fill out the matrices by giving their evaluations for the EDs of the support methods related to the controlling factors using a scale ranging from 1 (the worst) to 4 (the best). According to the scale a support method will have "very good" ED for the controlling factor when the degree is "4" and when the degree is "1", the method will not have sufficient efficiency degree to work for the con-

Support Methods		Side wall & Crown support					Face support				
		Rock bolts	Dowels	Steel arch	Sprayed concrete	Precast concrete segments	Forepoling	Pipe umbrella	Doorframe slab	Earth wedge	Sprayed concrete
Factors											
Cost / 1m length of tunnel											

Table (2): Comparing between support methods based on cost

Support Methods		Side wall & Crown support					Face support				
		Rock bolts	Dowels	Steel arch	Sprayed concrete	Precast concrete segments	Forepoling	Pipe umbrella	Doorframe slab	Earth wedge	Sprayed concrete
Factors											
Production rate = 75m/week											

Table (3): Comparing between support methods based on time

<p><u>Select one option for each factor</u></p> <p><u>Tunnel span</u></p> <p><input type="checkbox"/> 1.5m or less</p> <p><input type="checkbox"/> 2.0 - 4.0m</p> <p><input type="checkbox"/> 5.0 - 6.0m</p> <p><input type="checkbox"/> 7.0 - 10.0m</p> <p><input type="checkbox"/> over 10m</p>
<p><u>RMR value</u></p> <p><input type="checkbox"/> 0 - 20</p> <p><input type="checkbox"/> 21 - 40</p> <p><input type="checkbox"/> 41 - 60</p> <p><input type="checkbox"/> 61 - 80</p> <p><input type="checkbox"/> over 80</p> <p><input type="checkbox"/> ground is soil</p>
<p><u>Select failure reasons (you can select more than one reason)</u></p> <p><input type="checkbox"/> failure due to weathering</p> <p><input type="checkbox"/> failure due to moving water</p> <p><input type="checkbox"/> failure due to support corrosion</p> <p><input type="checkbox"/> failure due to squeezing and swelling</p> <p><input type="checkbox"/> failure due to overstress</p>
<p><u>Tunnel depth</u></p> <p><input type="checkbox"/> 30m or less</p> <p><input type="checkbox"/> 31 - 50m</p> <p><input type="checkbox"/> 51 - 100m</p> <p><input type="checkbox"/> 101 - 500m</p> <p><input type="checkbox"/> 501 - 1000m</p> <p><input type="checkbox"/> over 1000m</p>
<p><u>Tunnel cross section profile</u></p> <p><input type="checkbox"/> circular or mouth profile</p> <p><input type="checkbox"/> oval or horseshoe</p> <p><input type="checkbox"/> other profiles</p>
<p><u>Tunnel excavation method</u></p> <p><input type="checkbox"/> excavator / front shovel / backhoe</p> <p><input type="checkbox"/> hand excavation</p> <p><input type="checkbox"/> drill & blasting</p> <p><input type="checkbox"/> roadheader</p> <p><input type="checkbox"/> micro-tunnelling machine</p> <p><input type="checkbox"/> shield machine</p> <p><input type="checkbox"/> TBM (open machine)</p>

Table (4): Technical data of the project

trolling factor. "4" is the maximum efficiency degree used in the model. Four construction companies, two designers and two clients filled out and returned back the matrices. After collecting the data, average matrices were developed based on the experts' evaluations and

their notes. The ED values in the average matrices are the average values of the experts' EDs, the model uses these average EDs for the calculations of the support methods' EPs. The user of the model should feed it with technical data of the particular project to

enable the model in determining which ED values will be used for the calculations. The form of table (4) is used to collect the project technical data which are needed for selecting the support method. When the user selects the values which represent the project conditions, the model will use the EDs which correspond to the project conditions, for the calculations.

Importance percentages (IPs) of the controlling factors: The IPs of the controlling factors which will be calculated in this section represent the relative importance of each controlling factor compared to the importance of the other factors which control the selection of the support method.

The criterion affecting the magnitude of the controlling factor is "how much does the factor control the selection decision of support methods?" The user of the model has to answer this question when he/she determines the importance degree (ID) of each controlling factor. The IDs which will be determined by the user will be used to calculate the IPs of the controlling factors.

The scale of the ID is between zero and ten where a zero value indicates that the controlling factor is not important for selecting the support method. The most important controlling factors should be assigned the highest ID which is ten. The higher the ID value the higher the role of the controlling factor in the selection process.

The model uses equation (1) to calculate the IPs of the controlling factors using the ID values which are assigned by the user. The user will assign the IDs of the controlling factors using the form shown in table (5).

$$IP_i = \frac{ID_i}{\sum_{i=1}^n ID_i} * 100$$

Where: IP_i = importance percentage of factor "i"; ID_i = importance degree of factor "i" which is given by the user of the model; n = total number of factors.

A controlling factor named "Others" is added to the controlling factors. This factor represents the factors that may have an influence on the selection decision of the support method, from user's point of view, and these factors are not included among the con-

IDs given by the user	Controlling factors	Sub-Factors will have the same ID of the parent factors	ID that will be used in the model
X1	Ground conditions	RMR value	X1
		Failure due to weathering	X1
		Failure due to moving water	X1
		Failure due to corrosion of support	X1
		Failure due to squeezing & swelling	X1
		Failure due to overstress	X1
X2	Tunnel depth	-----	X2
X3	Tunnel shape	-----	X3
X4	Tunnel span	-----	X4
X5	Tunnel excavation method		X5
X6	Cost	-----	X6
X7	Time	-----	X7
X8	Others	-----	X8
Total number of ID values			n = 13 values

Table (5): Form used to assign IDs to the factors




Figure (1): Calculations of support methods' efficiency percentages

trolling factors. If the user assigns an ID to this factor in the form of table (5) he/she should assign EDs for the support methods related to the factor "Others". The model will assign the IDs of the controlling factors to their sub-factors, for example the ID for ground conditions "X1" will be assigned to the "RMR-value" factor and the failure modes factors (see table (5)).

Calculations of the support methods' EPs: Calculation of the EP for any support method has two steps. At first, the model calculates weighted efficiencies of the method for each controlling factor by multiplying the IP of the controlling factor by the ED of the method for that controlling factor. Equation (2) illustrates how to calculate the weighted efficiency of a support method "A" for a controlling factor "i", this calculation will be repeated "n" times which is the number of controlling factors for support method "A" (see figure 1). The second step of the calculations includes dividing the summation of the weighted efficiencies by the maximum efficiency degree to determine the EP of the support method. Equation (3) illustrates the second step of the calculations. When the calculated EP of a support method is zero, this means that this support method could not satisfy one or more of the project's controlling factors. The model ranks the

support methods with non-zero EPs in descending order. The following example illustrates the calculation steps.

$$W_{Ai} = ED_{Ai} * \frac{IP_i}{100}$$

$$EP_A = \frac{\sum_{i=1}^n W_{Ai}}{T} * 100$$

Where: "A" = a support method such as "Rock bolts", "Shotcrete", or "Forepoling" etc.; = the weighted efficiency of support method "A" for controlling factor "i"; = efficiency degree of support method "A" for controlling factor "i"; = importance percentage of the controlling factor "i" related to the other controlling factors; = the maximum efficiency degree which is "4"; = efficiency percentage of support method "A"; i = controlling factors of support methods; and n = number of controlling factors for support methods.

Example: If "A" and "B" are two support methods and they have the EDs shown in table (6) for controlling factors "X" and "Y". The maximum efficiency degree is "4" and the IPs of factors "X" and "Y" are 70% and 30%

respectively. Calculation of the weighted efficiency of method "A" for controlling factor "X" is as follows (application of equation 2):

- $ED_{AX} = 3$ (this value is shown in tab. 6), and $IP_X = 70\%$
- $W_{AX} = 3 * 0.7 = 2.1$ (this value is the weighted efficiency of method "A" for factor "X")

The weighted efficiency of method "A" for factor "Y" will be calculated as follows:

- $ED_{AY} = 2$ (this value is shown in tab. 6), and $IP_Y = 30\%$
- $W_{AY} = 2 * 0.3 = 0.6$ (this value is the weighted efficiency of method "A" for factor "Y")

The total weighted efficiency of method "A" = $W_{AX} + W_{AY} = 2.1 + 0.6 = 2.7$. The same calculations will be done for method "B" (see tab.7). The EP of method "A" = $2.7/4 * 100 = 67.5\%$, where "4" is the maximum efficiency degree (application of equation 3). The EP of method "B" = $2.6/4 * 100 = 65\%$. The calculations show that method "A" has marginally higher efficiency percentage (EP) than method "B".

„Application of the model.“

A computer program was developed to facilitate the use of the model. The program is written using Visual Basic 6 programming language. Data of three real projects were used to check the model validity. Projects that were used are "Wienerwald tunnel (Austria)", "U2/2 Taborstraße (Austria)" and "Gotthard tunnel - Amsteg section lot 252 (Switzerland)". Table (8) shows the results of the model compared with the support methods that are used really in the projects.

As shown in table (8) the support methods which have the highest EPs and they are suggested by the model for the "Wienerwald tunnel" project, and the "U2/2 Taborstraße" project are similar to the methods that are used in the project. There is a difference between the results of the model and the real case in the "Gotthard tunnel - Amsteg section lot 252" project. For this project, the model suggests the use of the "Precast concrete segments" as the most efficient method for the project and the "Sprayed concrete" comes in the second rank. In the real project the "Sprayed concrete" is used. This difference in results is not significant taking into consideration

Angaben zum Autor

Name

O.Univ.Prof. DI Dr.techn. Hans Georg JODL

Zur Person

1976 Studienabschluss Bauingenieurwesen an der Technische Hochschule Wien, 1991 Promotion zum Doktor der technischen Wissenschaften, 1992 Ordentlicher Universitätsprofessor für Baubetrieb und Bauverfahrenstechnik, 1993 Befugnis Zivilingenieur für Bauwesen (derzeit ruhend).

Umfangreiche Praxis in Kalkulation, Bauvorbereitung, Baustellenmanagement, Projektmanagement, Controlling, Bauleitung und Geschäftsführung während der Tätigkeit bei der Baufirma Allgemeine Baugesellschaft A. PORR AG in den Jahren 1976 bis 1992. Besondere Kenntnisse in Planung, Ausführung und Beratung auf den Gebieten Erd- und Wasserbau, Hohlraumbau/ Tunnelbau in Fest- und Lockergestein nach NATM, grabenloser Leitungsbau, Qualitäts- und Sicherheitsmanagement. Beratung in baubetrieblichen und bauwirtschaftlichen Fragen seit 1992. Privat-, Gerichts- und Schiedsgutachten, Schiedsrichter im ON-Schiedsgericht. Tunnelbautechnischer Sachverständiger.

that the difference between efficiency percentages of the "Precast concrete segments" and the "Sprayed concrete" as resulted from the model was not big at the same time the model suggests the support method in the conceptual phase of the project and further studies should be done before the final decision. The results of the model prove its validity and soundness of the program.

„Acknowledgement“

The authors would like to acknowledge Professor Herbert H. Einstein, Department of Civil and Environmental Engineering, Massachusetts Institute of Technology, Cambridge, USA, for

his valuable contribution and opinions that helped in finishing this work. The authors thank also the staff of the pro-

jects, which used for testing the model, for their help and supplying us with the required information.

Factors \ Methods	A	B
X	$3 * 0.7 = 2.1$	$2 * 0.7 = 1.4$
Y	$2 * 0.3 = 0.6$	$4 * 0.3 = 1.2$
Total weighted efficiencies	$2.1 + 0.6 = 2.7$	$1.4 + 1.2 = 2.6$

Table (7) Weighted efficiencies of methods "A" and "B"

Project \ Methods	Support method used in the project	Support method selected by the model
Wienerwald tunnel	Precast concrete segments	Precast concrete segments
U2/2 Taborstraße	Sprayed concrete	Sprayed concrete
Gotthard tunnel - Amsteg section lot 252	Sprayed concrete	Precast concrete segments

Table (8) Comparison between the results of the model and the support methods used in the projects

References

- Barton, N., Lien, R., and Lunde, J. 1974. "Engineering Classification of Rock Masses for the Design of Tunnel Support", *Rock Mechanics*, Vol. 6, No. 4.
- Bieniawski, Z.T. 1976. "Rock mass classification in rock engineering", In *Exploration for rock engineering*, proc. of the symp., (ed. Z.T. Bieniawski) 1, 97-106. Cape Town: Balkema.
- Bieniawski, Z.T. 1989. "Engineering rock mass classifications", Wiley, New York.
- Deere, D. U., Peck, R. B., Parker, H. W., Monsees, J. E., and Schmidt, B. 1970. "Design of Tunnel Support Systems", *Highway Res. Rec. No. 339*:26-33.
- Grimstad, E. and Barton, N. 1993. "Updating the Q-System for NMT", *Proc. int. symp. On sprayed concrete - modern use of wet mix sprayed concrete for underground support*, Fagernes, (eds Kompen, Opsahl and Berg). Oslo: Norwegian Concrete Assn.
- Lauffer, H. 1958. "Gebirgsklassifizierung für den Stollenbau", *Geol. Bauwesen*, 24(1), 46-51.
- Terzaghi, K. 1946. "Rock Defects and Loads on Tunnel Support", *Rock Tunnelling with Steel Support*, R. V. Proctor and T. White, Commercial Shearing Co., Youngstown, OH: 15-99.
- Toma, H. 2005. "A computer model for selecting efficient tunnelling systems", PhD dissertation, Faculty of Civil Engineering, Vienna University of Technology, Vienna, Austria.
- Wickham, G. E., Tiedemann, H. R., and Skinner, E. H. 1972. "Support Determinations Based on Geologic Predictions", *Proceedings, First Rapid Excavation and Tunnelling Conference*, Chicago, VOII.
- Vavrovsky, G-M., Schubert, W., Ayaydin, N., and Schwab, P. 2001. "Richtlinie für die Geomechanische Planung von Untertagebauarbeiten mit zyklischem Vortrieb" *Österreichische Gesellschaft für Geomechanik (Ed.)*, Salzburg

