

Radar interferometric observations of permafrost related surface deformation

T. Strozzi & U. Wegmüller

Gamma Remote Sensing, Worbstrasse 225, 3073 Gümligen, Switzerland, {strozzi,wegmuller}@gamma-rs.ch

Reynald Delaloye

Department of Geosciences - Geography, University of Fribourg, Ch. du Musée 4, 1700 Fribourg, Switzerland, reynald.delaloye@unifr.ch

Hugo Raetzo

Federal Office for the Environment, Postfach, 3003 Bern, Switzerland, hugo.raetzo@bafu.admin.ch

Andrew Kos

Geologisches Institut, ETH Zürich, Sonneggstrasse 5, 8092 Zürich, Switzerland, andrew.kos@erdw.ethz.ch

Annett Bartsch

Institute of Photogrammetry and Remote Sensing, Vienna University of Technology, Gusshausstrasse 27 - 29, 1040 Vienna, Austria, ab@ipf.tuwien.ac.at

Christophe Lambiel

Institute of Geography, University of Lausanne, Bâtiment Anthropole, 1015 Lausanne, Switzerland, christophe.lambiel@unil.ch

ABSTRACT

In recent years we successfully applied radar interferometry to measure surface deformation over permafrost areas. The first investigations concerned the estimation of the surface deformation of rockglaciers in the Swiss Alps between 1995 and 2000 using Synthetic Aperture Radar (SAR) data of the European Remote Sensing Satellites ERS-1 and ERS-2. Based on ERS differential interferograms, with a ground spatial resolution of about 20 m and a radar wavelength of 5.6 cm, an inventory of mass moving objects could be elaborated over a large part of the Swiss Alps. Rockglaciers were classified into the four displacement rate classes: cm's/day, dm's/month, cm's/month and cm's/year (Delaloye et al. 2007, Lambiel et al. 2008). More recent satellite SAR images of the ENVISAT ASAR, ALOS PALSAR and TerraSAR-X sensors permitted updating the inventory with respect to the more recent rockglacier activity, the spatial resolution (which is 3 m in the case of TerraSAR-X), and the detection of displacement at more densely vegetated lower altitudes (higher coherence of 23 cm wavelength of ALOS PALSAR). Considering that the quantification of displacement rates larger than about 0.5 cm/day is currently limited by the orbit repeat time interval of the satellites, radar interferometric observations with a ground-based instrument were also performed. Our ground-based radar interferometer operates from a tripod with a signal wavelength of 1.8 cm and a temporal interval of about 15 minutes (Werner et al. 2008), permitting the detailed survey of mass movements with displacement rates of

cm's/day like destabilized rockglaciers and rockwalls (Strozzi et al. 2009). Furthermore, preliminary encouraging results using TerraSAR-X data for the monitoring of Arctic permafrost subsidence over an area around Tuktoyaktuk near the Mackenzie River Delta in Canada will be presented.

References

- Delaloye, R., Lambiel, C., Lugon, R., Raetzo, H., Strozzi, T. (2007). Typical ERS InSAR signature of slope movements in a periglacial mountain environment (Swiss Alps). Proc. 'Envisat Symposium 2007', Montreux, Switzerland 23–27 April 2007 (ESA SP-636, July 2007), 3P7.
- Lambiel, C., Delaloye, R., Strozzi, T., Lugon, R., Raetzo, H. (2008). ERS InSAR for detecting the rockglacier activity. Proceedings of the Ninth International Conference on Permafrost, July 2008, Fairbanks, Alaska, 1, 1019-1024.
- Strozzi, T., Delaloye, R., Raetzo, H., Wegmüller, U. (2009). Radar interferometric observations of destabilized rockglaciers. Proceedings of the FRINGE 2009 Workshop, Frascati, Italy.
- Werner, C., Strozzi, T., Wiesmann, A., Wegmüller, U. (2008). GAMMA's portable radar interferometer. Proceedings of IAG/FIG, Lisbon, Portugal.