



Brescia, Italy 5-8 September 2011

IABEM 2011



CeSiA

Symposium of the  
International Association for Boundary Element Methods

## Residual A-Posteriori Error Estimates in BEM: Convergence of $h$ -Adaptive Algorithms

M. Feischl, M. Karkulik, J.M. Melenk, and D. Praetorius

Vienna University of Technology, Institute for Analysis and Scientific Computing

Michael.Karkulik@tuwien.ac.at

### Abstract

Galerkin methods for FEM and BEM based on uniform mesh refinement have a guaranteed rate of convergence. Unfortunately, this rate may be suboptimal due to singularities present in the exact solution. In numerical experiments, the optimal rate of convergence is regained when algorithms based on a-posteriori error estimation and adaptive mesh-refinement are used. This observation was proved mathematically for the FEM in the last few years, cf. [5]. In contrast, the mathematical understanding of adaptive strategies is wide open in BEM. One reason for this is the non-locality of the boundary integral operators involved and the appearance of fractional-order or negative Sobolev norms.

In our prior works on adaptive BEM [1], we considered  $h - h/2$  error estimators. Reliability of such estimators is, however, equivalent to the so-called saturation assumption. Although this is widely believed to hold in practice, it still remains mathematically open. For this reason, these convergence results are not fully satisfactory.

In our talk, we consider weighted residual error estimators for some weakly-singular integral equations in 2D or 3D. These estimator are reliable, irrespective of the saturation assumption. We prove a certain (local) inverse-type estimate which allows us to conclude that the discrete solutions generated by the usual  $h$ -adaptive algorithm converge towards the exact solution of the integral equation. In a second step we prove quasi-optimality in a certain approximation class. From this, we infer that the rate of convergence of adaptive mesh-refinement is at least as good as for uniform approaches.

# 1 Boundary element method

## 1.1 Model problem

For a bounded Lipschitz domain  $\Omega \subset \mathbb{R}^3$  with boundary  $\Gamma$ , we consider the Dirichlet problem

$$\begin{aligned} -\Delta u &= 0 & \text{in } \Omega, \\ u &= g & \text{on } \Gamma. \end{aligned} \tag{1}$$

The given boundary data satisfies  $g \in H^{1/2}(\Gamma)$ . By  $\langle \cdot, \cdot \rangle$ , we denote the extended  $L_2(\Gamma)$ -scalar product. Problem (1) is equivalently stated as boundary integral equation

$$\langle V\phi, \psi \rangle = \langle f, \psi \rangle \quad \text{for all } \psi \in H^{-1/2}(\Gamma) \tag{2}$$

with  $f = (K + 1/2)g$ . Here,  $V$  and  $K$  denote the simple- and double-layer potential

$$\begin{aligned} (V\psi)(\mathbf{x}) &= \int_{\Gamma} G(\mathbf{x} - \mathbf{y})\psi(\mathbf{y})d\Gamma(\mathbf{y}), \\ (Kv)(\mathbf{x}) &= \int_{\Gamma} \partial_{n(\mathbf{y})}G(\mathbf{x} - \mathbf{y})v(\mathbf{y})d\Gamma(\mathbf{y}) \end{aligned}$$

with the fundamental solution  $G(x) = \frac{1}{4\pi|x|}$  of the 3D-Laplacian. Equation (2) has a unique solution  $\phi$  which depends continuously on the given data. The link between (1) and (2) is provided by  $\phi = \partial_n u$ . The operator  $V$  is symmetric and elliptic and thus induces an energy norm  $\|\cdot\|$  via

$$\|\phi\|^2 := \langle V\phi, \phi \rangle.$$

## 1.2 Galerkin boundary element method


Replacing the infinite-dimensional space in (2) by some finite element space leads to the Galerkin formulation: Find  $\Phi_\ell \in \mathcal{P}^0(\mathcal{E}_\ell)$  such that

$$\langle V\Phi_\ell, \Psi_\ell \rangle = \langle f, \Psi_\ell \rangle \quad \text{for all } \Psi_\ell \in \mathcal{P}^0(\mathcal{E}_\ell). \tag{3}$$

Here,  $\mathcal{E}_\ell$  is a mesh on  $\Gamma$ , and  $\mathcal{P}^0(\mathcal{E}_\ell)$  is the space of piecewise constant functions on  $\mathcal{E}_\ell$ . We introduce  $h_\ell(E) := |E|^{1/2}$  to be the square root of the area of  $E \in \mathcal{E}_\ell$ . The local mesh width function  $h_\ell \in L_\infty(\Gamma)$  is defined as  $h_\ell|_E := h_\ell(E) = |E|^{1/2}$ . The Galerkin equation (3) allows for a unique solution  $\Phi_\ell$  by solving a linear system of equations.

## 2 Convergent adaptive algorithm

For the efficient solution of (3), we propose to use an adaptive algorithm of the type



Having computed the Galerkin solution  $\Phi_\ell$  in step `solve`, we use the weighted-residual a-posteriori error estimator  $\mu_\ell$  of [4] in step `estimate` to measure the local energy error. The estimator is defined elementwise as

$$\mu_\ell^2 := \sum_{E \in \mathcal{E}_\ell} \mu_\ell(E)^2 \quad \text{with } \mu_\ell(E)^2 := h_\ell(E) \|\nabla_\Gamma(V\Phi_\ell - f)\|_{L_2(E)}^2,$$

and it was shown in [4] that  $\mu_\ell$  is reliable, i.e.,

$$\|\phi - \Phi_\ell\| \lesssim \mu_\ell. \quad (4)$$

With  $\ell := 0$ , an initial mesh  $\mathcal{E}_0$  and the parameter  $0 < \theta < 1$  as input, the adaptive algorithm now takes the following form:

- (i) Compute the Galerkin solution  $\Phi_\ell$  on the mesh  $\mathcal{E}_\ell$ .
- (ii) Compute refinement indicator  $\mu_\ell(E)$  for all  $E \in \mathcal{E}_\ell$
- (iii) Determine the set  $\mathcal{M}_\ell \subseteq \mathcal{E}_\ell$  such that

$$\sum_{E \in \mathcal{M}_\ell} \mu_\ell(E)^2 \geq \theta \sum_{E \in \mathcal{E}_\ell} \mu_\ell(E)^2, \quad (5)$$

under the condition that  $\mathcal{M}_\ell$  has minimal cardinality.

- (iv) Refine at least elements in  $\mathcal{M}_\ell$  by newest-vertex-bisection to obtain  $\mathcal{E}_{\ell+1}$ .
- (v)  $\ell := \ell + 1$ , goto (i).

The marking criterion (5) has been introduced in [6]. In [5], it is shown that (5) is in some sense even necessary for quasi-optimality of adaptive FEM.

A first important observation from [2] is that the computed discrete solutions converge to some limit and thus fulfill

$$\|\Phi_\ell - \Phi_{\ell+1}\| \rightarrow 0 \quad \text{as } \ell \rightarrow \infty. \quad (6)$$

To prove that this limit coincides with  $\phi$ , we show  $\mu_\ell \rightarrow 0$  and use (4). In [7], we prove that the adaptive algorithm ensures

$$\mu_{\ell+1}^2 \leq \tilde{\kappa} \mu_\ell^2 + C \|h_{\ell+1}^{1/2} \nabla_\Gamma V (\Phi_{\ell+1} - \Phi_\ell)\|_{L_2(\Gamma)}^2 \quad (7)$$

with some  $0 < \tilde{\kappa} < 1$  and  $\tilde{\kappa} \simeq (1 - \theta(1 - q))$ . Here,  $q$  describes the shrinking factor of the mesh width  $h_\ell$  on refined elements. Since marked elements are at least split into 2 sons with at most halve area, we have  $q = 1/2$ . To estimate the last term in (7), we provide the novel inverse inequality

$$\|h_k^{1/2} \nabla_\Gamma V \Psi_k\|_{L_2(\Gamma)} \lesssim \|\Psi_k\| \quad \text{for all } \Psi_k \in \mathcal{P}^0(\mathcal{E}_k). \quad (8)$$

We stress that on quasi-uniform meshes, (8) follows immediately from the theory of interpolation spaces. On locally refined meshes, the proof of (8) is much more technical due to the non-locality of  $V$  and the fact that  $\|\cdot\|$  is equivalent to a negative Sobolev norm of fractional order. Choosing  $k = \ell + 1$  and  $\Psi_k = \Phi_{\ell+1} - \Phi_\ell$  in (8) yields the so-called *estimator reduction*

$$\mu_{\ell+1}^2 \leq \tilde{\kappa} \mu_\ell^2 + C \|\Phi_{\ell+1} - \Phi_\ell\|^2. \quad (9)$$

Together with (6), the estimator reduction can be written in Landau-notation as

$$\mu_\ell^2 \leq \tilde{\kappa} \mu_\ell^2 + o(1),$$

and elementary calculus shows  $\mu_\ell \rightarrow 0$ , i.e. the discrete solutions computed from the adaptive algorithm converge to the exact solution of the boundary integral equation. From (9), we conclude in [7] that a weighted sum of energy error and error estimator, the so-called quasi-error, is indeed a contraction. This is a stronger result than pure convergence, because the quasi-error is reduced uniformly in every step.

**Theorem 1** *There are constants  $0 < \kappa, \lambda < 1$  such that the quasi-error is contractive, i.e.*

$$\Delta_{\ell+1} \leq \kappa \Delta_\ell \quad \text{with } \Delta_\ell := \|\phi - \Phi_\ell\|^2 + \lambda \mu_\ell^2. \quad (10)$$

*The constants  $\kappa$  and  $\lambda$  do not depend on  $\phi$  or  $\ell$ . In particular, this implies convergence*

$$\|\phi - \Phi_\ell\| \rightarrow 0 \quad \text{as } \ell \rightarrow \infty.$$

### 3 A Quasi-Optimality Result

Contemporary proofs of quasi-optimality of adaptive FEM mainly follow [5] and have three main ingredients:

- (I) The contraction property for the quasi-error, cf. Theorem 10,
- (II) the optimality of the marking strategy (5),
- (III) and the definition of a proper approximation class.

The proof of (II), i.e. the optimality of the marking strategy, needs the *discrete local reliability* of the error estimator. It states that, for two successive meshes, the difference of the corresponding Galerkin solutions is bounded by the error estimator on the refined elements. In contrast to the FEM, the energy norm  $\|\cdot\|$  is equivalent to the non-local norm  $\|\cdot\|_{H^{-1/2}(\Gamma)}$ , which introduces technical difficulties. Nevertheless, the discrete local reliability of  $\mu_\ell$  can be proven. We emphasize that the set  $\mathcal{E}_\ell \setminus \mathcal{E}_\star$  in the next Lemma is actually the set of elements from  $\mathcal{E}_\ell$  that are refined when  $\mathcal{E}_\ell$  is refined to  $\mathcal{E}_\star$ . The set  $\mathcal{R}_\ell$  is basically this last set plus one additional layer of elements.

**Lemma 1** *Let  $\mathcal{E}_\star$  be an arbitrary refinement of  $\mathcal{E}_\ell$  with corresponding Galerkin solution  $\Phi_\star \in \mathcal{P}^0(\mathcal{E}_\star)$ . Then,*

$$\|\Phi_\star - \Phi_\ell\|^2 \lesssim \sum_{E \in \mathcal{R}_\ell} \mu_\ell(E)^2.$$

*Here,  $\mathcal{R}_\ell := \{E \in \mathcal{E}_\ell : \exists E' \in \mathcal{E}_\ell \setminus \mathcal{E}_\star : E \in \omega_\ell(E')\}$ , and  $\omega_\ell(E')$  is the patch of all elements touching  $E'$ .*

So far, we have proven in Theorem 1 that the marking criterion (5) implies a contraction of  $\Delta_\ell$ . The following proposition states the converse implication, i.e. the ingredient (II) is available.

**Proposition 1** *There are constants  $0 < \kappa_\star, \theta_\star < 1$  such that for all  $0 < \theta \leq \theta_\star$  and all refinements  $\mathcal{E}_\star$  of  $\mathcal{E}_\ell$  holds*

$$\Delta_\star \leq \kappa_\star \Delta_\ell \implies \theta \sum_{E \in \mathcal{E}_\ell} \mu_\ell(E)^2 \leq \sum_{E \in \mathcal{R}_\ell} \mu_\ell(E)^2,$$

i.e. the set  $\mathcal{R}_\ell$  defined in Lemma 1 satisfies the marking criterion (5). The constants  $\kappa_\star, \theta_\star$  do not depend on  $\ell$ .

In [5], the point (III) contains the definition of an *optimal* approximation class, i.e. a prescribed accuracy for the approximation error should be reached with the optimal order of complexity of the corresponding Galerkin method. Note that the adaptive algorithm only sees the estimator  $\mu_\ell$ , thus it is necessary to link  $\mu_\ell$  to the approximation error introduced within the approximation class. This leads us to the definition of *oscillation*. In adaptive FEM, it can be proven that, on locally refined meshes,

$$\eta_\ell \simeq \|||u - U_\ell\||| + \text{osc}_\ell \quad (11)$$

for the residual error estimator  $\eta_\ell$ , the exact solution  $u$  and the FEM-solution  $U_\ell$ . The term  $\text{osc}_\ell$  is of higher order compared to  $\|||u - U_\ell\|||$ , and thus the right hand side of (11) is a prospective candidate for the definition of the approximation class.

Up to now, a result of the form (11) for BEM is available only on quasi-uniform meshes. Using an efficiency result from [3], we have in this special case the equivalence

$$\mu_\ell \simeq \|||\phi - \Phi_\ell\|||. \quad (12)$$

On locally refined meshes, we provide a weak efficiency result of the form

$$\mu_\ell \simeq \|||\phi - \Phi_\ell\||| + \text{osc}_\ell,$$

with an oscillation term  $\text{osc}_\ell$  that is generically not of higher order. We then use the right hand side as approximation error in an artificial approximation class.

Let  $\mathbb{T}_N$  be the set of all meshes  $\mathcal{E}$  with at most  $\#\mathcal{E} = N$  elements, which can be generated from the initial mesh  $\mathcal{E}_0$  by newest-vertex-bisection. We introduce the approximation class

$$\mathbb{A}_s := \left\{ \phi : |\phi|_s := \sup_{N>0} \left( N^s \inf_{\mathcal{E}_\star \in \mathbb{T}_N} \mu_\star \right) < \infty \right\}. \quad (13)$$

Here,  $\mu_\star$  denotes the weighted-residual error estimator with respect to  $\mathcal{E}_\star$ . The interpretation of this definition is the following: If  $\phi \in \mathbb{A}_s$ , then the estimator  $\mu_\ell$  and in particular the error  $\|||\phi - \Phi_\ell\|||$  can be as small as  $\epsilon > 0$  with  $\mathcal{O}(\epsilon^{-s})$  elements.

In [7], we prove the following quasi-optimality result:

**Theorem 2** *For sufficient small adaptivity parameter  $\theta$ , the adaptive algorithm ensures*

$$\mu_\ell \lesssim \#\mathcal{E}_\ell^{-s}$$

*provided that  $\phi \in \mathbb{A}_s$  for some  $s > 0$ . With reliability (4), this yields*

$$\|\phi - \Phi_\ell\| \lesssim \#\mathcal{E}_\ell^{-s}$$

The consequence is the following: If a uniform approach yields  $\|\phi - \Phi_\ell\| = \mathcal{O}(N^{-t})$  for some  $t > 0$ , then it follows from (12) that  $\phi \in \mathbb{A}_t$ . But then our result (2) states that the adaptive algorithm also achieves an order of convergence  $\mathcal{O}(N^{-t})$ . This concludes that the adaptive algorithm achieves at least the same order of convergence as the uniform approach.

## ***Acknowledgements***

The research of the authors M. Feischl, M. Karkulik, and D. Praetorius is supported through the FWF project Adaptive Boundary Element Method, funded by the Austrian Science Fund (FWF) under grant P21732.

## ***References***

- [1] Aurada, M., Ferraz-Leite, S., Goldenits, P., Karkulik, M., Mayr, M., Praetorius, D. “Convergence of adaptive BEM for some mixed boundary value problem”, *Appl. Numer. Math.*, In Press, Available online 29 March, 2011.
- [2] Babuška, I., Vogelius, M., “Feedback and adaptive finite element solution of one-dimensional boundary value problems”, *Numer. Math.*, **44**, 75-102, 1984.
- [3] Carstensen, C., “Efficiency of a posteriori BEM-error estimates for first-kind integral equations on quasi-uniform meshes,” *Math. Comp.*, **65**(213), 69-84, 1996.
- [4] Carstensen, C., Maischak, M., Stephan, E.P., “A posteriori error estimate and  $h$ -adaptive algorithm on surfaces for Symm’s integral equation,” *Numer. Math.*, **90**(2), 197-213, 2001.
- [5] Cascon, J.M., Kreuzer, C., Nochetto, R.H., and Siebert, K. G., “Quasi-optimal convergence rate for an adaptive finite element method,” *SIAM J. Numer. Anal.*, **46**(5), 2524-2550, 2008.
- [6] Dörfler, W., “A convergent adaptive algorithm for Poisson’s equation”, *SIAM Numer. Anal.*, **33**, 1106-1124, 1996.
- [7] Feischl, M., Karkulik, M., Melenk, J.M., and Praetorius, D., “Convergence of adaptive boundary element method driven by some weighted residual error estimator,” *work in progress*, 2011.